


## PUSH-TO-START

# COMMERCIAL STACK DRYER

### Built for Reliable Performance

Speed Queen's stack dryer offers the same great features as the single load dryer. Two commercial dryers in the space of one, both operating independently, including independent controls for optimum usage. They're designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. Our cabinet design maintains the perfect balance of heat, airflow and tumble action for optimal performance and efficiency. The equipment provides an advantage on such issues as energy conservation, equipment breakdowns and vandalism. The dry cycle is efficient and fast. Customers have the flexibility to choose from four heat/cycle selections. Bottom dryer is ADA compliant.

- Industry's largest door opening 2.06 sq. ft. (1914 cm<sup>2</sup>)
- Quiet, efficient blower system
- Door is reversible for installation flexibility
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)
- 100% serviceable from the front
- Space-saving narrow cabinet 26.875" (683 mm)
- Upfront lint filter easy to clean and secured
- Durable galvanized steel cylinder





Push-to-Start control provides easy to start activation indicated by "In Use" light.

SPECIFICATIONS

# COMMERCIAL STACK DRYER

|                                                           |                                                         |
|-----------------------------------------------------------|---------------------------------------------------------|
| MODEL - see below for all models and activation available |                                                         |
| CONTROL OPTION                                            | Push-to-Start                                           |
| COLOR                                                     | White                                                   |
| CAPACITY - lb (kg)                                        | 18 (8.2) ea                                             |
| CYLINDER VOLUME - cu. ft. (liters)                        | 7.0 (198) ea                                            |
| MOTOR (THERMAL PROTECTED)                                 | 0.33 HP                                                 |
| TYPE OF GAS (GAS MODELS ONLY)                             | Factory equipped natural/mixed gas                      |
| AIR OUTLET DIAMETER - in (mm)                             | 4 (102)                                                 |
| EXHAUST AIRFLOW - cfm (liters/sec)                        | 220 (105)                                               |
| CYCLE SELECTIONS                                          | Normal, Perm Press<br>Delicate, No Heat                 |
| ELECTRICAL REQUIREMENTS ♦                                 | Electric 120/240/60/1-30 amp<br>120/208/240/60/1-30 amp |
|                                                           | Gas 120/60/1-15 amp                                     |
| HEATING ELEMENT                                           | Electric 5350W, 240V<br>4750W, 208V                     |
|                                                           | Gas 25,000 Btu                                          |
| NET WEIGHT - lb (kg)                                      | Electric 262 (119)                                      |
|                                                           | Gas 262 (119)                                           |
| SHIPPING WEIGHT lb (kg)                                   | Electric 272 (123.4)                                    |
|                                                           | Gas 272 (123.4)                                         |
| SHIPPING DIMENSIONS APPROX. - in (mm)                     | Width 33 (838)                                          |
|                                                           | Depth 30 (762)                                          |
|                                                           | Height 80 (2032)                                        |
| AGENCY APPROVALS                                          | Electric cULus                                          |
|                                                           | Gas cCSAus                                              |

| MODELS         | VOLTAGE/FREQ/PH | ACTIVATION                                                                                                 |
|----------------|-----------------|------------------------------------------------------------------------------------------------------------|
| SSEMAGS173TW01 | 120/240/60/1    | Electric Push-to-Start  |
| SSEMAGS153TW01 | 120/208/60/1    |                                                                                                            |
| SSGMAGS113TW01 | 120/60/1        |                                                                                                            |



|    |                                |              |
|----|--------------------------------|--------------|
| A. | OVERALL WIDTH - in (mm)        | 26.875 (683) |
| B. | OVERALL DEPTH - in (mm)        | 28 (711)     |
| C. | OVERALL HEIGHT - in (mm)       | 78.17 (1986) |
| D. | FLOOR TO DOOR OPENING -in (mm) | 15.44 (392)  |
| E. | DOOR SWING - in (mm)           | 23.5 (597)   |

♦ NOTE: Each stack dryer pocket requires its own separate power cord (not supplied).

■ Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.



by Alliance Laundry Systems

[speedqueencommercial.com/multihousing](http://speedqueencommercial.com/multihousing)

AM18-0126 • ©2018 Alliance Laundry Systems LLC