



Quantum[™] Gold

Prep for Card | Coin Drop Installed

Built for Reliable Performance

Speed Queen's stack washer/dryer brings an innovative stacked concept that takes up half the floor space that a conventional washer and dryer does when situated side by side. The freestanding softmount design can be installed on all floor types or levels. Both washer and dryer have the same hookups and connections as a standard washer and dryer. No additional plumbing or electrical change is needed. Speed Queen's stack washer/dryer combines heavy-duty construction with reliable operation proven to stand the test of time. They're designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. Front load products have met every design standard to be 100% ADA compliant.





- Integrated meter case
- Large capacity meter case standard
- Wash Alert™ capability

Washer (ADA Compliant)

- Rugged suspension system
- Industry leading 1200 RPM spin speed exerts 440 G-force extraction
- Durable stainless steel washtub
- Four-compartment soap dispenser
- Extra-wide 15.5["] door opening and 180° door swing Dryer
- Upfront lint filter easy to clean
- Industry's largest door opening 2.06 sq. ft. (1914 cm2)
- Quiet, efficient blower system




Quantum[™] Gold Control

The cutting edge Quantum[™] control system from Speed Queen[®] gives you the freedom to manage laundry your way with the power to achieve unmatched levels of revenue. Quantum[™] Gold provides users with additional cycle choices while offering new options to help lower operating costs and incorporates tools and options to increase revenue.

Stack Washer/Dryer – Short

Quantum[™] Gold

Specifications			
Control Option	Quantum Gold		
Color	White		
Capacity - lb (kg)	21.5 (9.5)		
	Dryer	18 (8.2)	
Overall Width - in (mm)	26.875 (683)		
Overall Depth - in (mm)	27.73 (704)		
Overall Height - in (mm)	76.5 (1943)		
Cylinder Volume	Washer	3.42 (96.8)	
cu. ft. (liters)	Dryer	7.0 (198)	
Motor Size - HP (kW)	0.9 (0.67)		
Type Of Gas (Gas Models Only	Natural gas		
Water Consumption Per Cycle	13.68 (51.78)		
IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**	4.0 (0.53)		
MEF, (Modified Energy Factor ft³/kWh/cycle (Liters/kWh/cycl	2.20 (62.3)		
Available Water Temperature	S	Hot, Warm, Cold	
Available Cycles	Light, Medium, Heavy, Normal, Perm Press, Delicates/Bulky		
	Dryer	High, Medium, Low, Delicate, No Heat	
Air Outlet Diameter - in (mm)	4 (102)		
Exhaust Airflow - cfm (liters/s	220 (105)		
Electrical	Electric	120/240/60/1-30 amp	
Requirements	Gas	120/60/1-15 amp	
Heating Element Electric		5350W, 240V 4750W, 208V	
	Gas	25,000 Btu	
Net Weight - lb (kg)	385 (175)		
Shipping Weight - lb (kg)		417 (189)	
	Width	34 (864)	
Shipping Dimensions Approx in (mm)	Depth	30 (762)	
	Height	80 (2032)	
	Electric	cULus	
Agency Approvals	Gas	cCSAus	



Α.	Overall Width - in (mm)	26.875 (683)
в.	Overall Depth - in (mm)	27.73 (704)
C.	Overall Height - in (mm)	76.5 (1943)
D.	Floor To Door Opening -in (mm)	14.5 (368)*
Ε.	Door Swing - in (mm)	23.5 (597)

* For ADA compliance turn legs out from base 0.5 inches

Models	Voltage/Freq/PH		Drain	Activation
STENCFSP175TW01	120/240/60/1	Electric	Pump	Coin
STGNCFSP115TW01	120/60/1	Gas	Pump	Installed
STENYFSP175TW01	120/240/60/1	Electric	Pump	Prep for
STGNYFSP115TW01	120/60/1	Gas	Pump	Card

Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

** Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.