



Yamamoto



Yamamoto North America



WUN70

Yamamoto North America
PO Box 3264
507 W Olive St
Bloomington, IL 61702-3264



866-204-0519
8 AM - 5 PM MON-FRI
www.yamamoto-na.com

Model No.		WUN70	
Capacity (Best Practices)		32 kg	70.0 lbs
Drum	Diameter	φ890 mm	φ35.0"
	Depth	461 mm	18.1"
	L/ Cubic Feet	286 L	10.1 cu.ft
	Pound capacity	70 lbs	
Machine Size (Packing Size)	Height	1714 mm (1900)	67.5" (74.9)
	Width	1146 mm (1300)	45.1" (51.2)
	Depth	1295 mm (1500)	51.0" (59.1)
Weight of empty machine		850 kg	1875 lbs
Crated Weight		905 kg	2000 lbs
Drum Speed	Washing Speed	20~50rpm	
	Extraction Speed	100~800rpm	
G - Force	High Speed	318 G	
Dynamic Loading	Frequency	13.3 Hz	
	Dynamic floor weight	1700kg/m ²	348.2lb/ft ²
Loading Door	Door Height	915 mm	36"
	Door Opening	φ475 mm	φ18.7"
Power	Electrical phase, Voltage, Frequency	3-phase, AC208~230V, 60Hz	
	Connection Port	1NPT	
Cold Water Supply	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
	Connection Port	1NPT	
Hot Water Supply	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
	Connection Port	1/2NPT	
Detergent Cup Water	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
	Connection Port	2•1/2NPT	
Steam	Supply Port	1/2NPT	
	Drain Port	3/8NPT	
	Pressure	0.4-0.6MPa , 58-87psi , 4-6bar	
Heating System		Hot Water Supply& Steam	
Usage environment	Temperature Surrounding Of	5-45°C , 41-113°F	
	Humidity	30-85%	
	Altitude	The machine should be installed in the altitude which is lower than in 3280 ft.	

